


JP4

NO.	SIGNAL
1	DC 12V
2	DC 5V OUTPUT
3	TX
4	RX
5	GND



DOT SIZE


J1

NO.	SIGNAL
1	VDD 5V
2	D-
3	D+
4	GND

NOTES:

1. DRIVE METHOD: 1/64DUTY, 1/9BIAS, VOP 11.5V,VDD 5.0V.
2. VIEWING ANGLE: 6 0'CLOCK.
3. DISPLAY TYPE: STN(BLUE), TRANSMISSIVE/NEGATIVE.
4. OPERATING TEMP: -20° TO 70°C.
5. STORAGE TEMP: -30° TO 80°C.
6. CONNECTION: ZEBRA.(Large panel is on top layer.)
7. INTERFACE: RS232.
8. BACK LIGHT:WHITE. EDGE
9. NOT DIMENSION TOLERANCES IS ±0.3.

日期	版本	修改内容
151104	01	依實際樣品，修正厚度標示



**晶發科技有限公司**  
GFI FAR TECHNOLOGY CO., LTD

DATE	2015.11.04	REV	01
UNIT : mm	Product :	<b>GFR240064E-BNFE(MD)</b>	
SCALE : 1/1	DRAWN :	Hazel	CHECKED : Donlin
SHEET : 1/1			PAGE: 1/1