


NOTE:
 1.(): REFERENCE DIMENSION.
 2.□: IMPORTANT DIMENSION.


Specification

1.LCD type: a-Si TFT , Normally White , TN mode , Positive / Transmissive
2.Driver IC: SSD2119 (262K Colors),VDD:3.3V
3.View direction: 6 O'CLOCK
4.Operating temp:-20°C~70°C, Storage temp: -30°C~80°C
5.Back light:6PCS White LED;Vf:19.2V;If:20mA Luminace(cd/m ²);without LCD 3500(min)
6.Back light Chromaticity Coordinales:X(w)0.28~0.34 / Y(w)0.28~0.34
7.FPC suggested connector:"Hirose" FH12S-50S-0.5SH(55) or compatible
8.The tolerance unless classified ±0.20mm
9.Remark:ROHS



Detail DOTS
Scale: 50/1

電路圖 CIRCUIT DIAGRAM (LED 6*1=6 dies)



Detail a
Scale: 5X

日期	版本	修改內容



晶發科技股份有限公司
GI FAR TECHNOLOGY CO., LTD.

DATE	2017.12.21	REV	00	DRAWING NO.:
UNIT : mm	Product :	GFTO035MA320240		
SCALE : 1 / 1	DRAWN :	Hazel	CHECKED :	Sidney
				PAGE : 1 / 1