



| Interface | | |
|-----------|--------|--|
| Pin no | Symbol | Function |
| 1 | RST | External reset pin |
| 2 | SCL | H/L Register select signal |
| 3 | SDA | Chip select (Low active) |
| 4 | VSS | Power supply (GND) |
| 5 | VDD | Power supply(+) |
| 6 | CAP1+ | For voltage booster circuit(VDD-VSS) External capacitor about 0.1u~4.7uf |
| 7 | CAP1- | |
| 8 | VOUT | DC/DC voltage converter. Connect a capacity between this terminal and VDD when the built-in booster is used. |

| Feature | | | | | | |
|----------------------------|-----------|----------------|---------------|---------|-------|-------|
| Controller | ST7032I | Module | 36.0 x 23.5 | | | |
| Duty | 1/16 duty | Viewing Area | 32.0 x 14.5 | | | |
| Bias | 1/4 bias | Mounting hole | - | | | |
| B/L | NO | Character Size | 2.945 x 5.545 | | | |
| Absolute Maximum Rating | | | | | | |
| Item | Symbol | Condition | Min | Max | Units | |
| Supply for logic voltage | Vdd-Vss | 25°C | -0.3 | 7 | V | |
| LCD driving supply voltage | Vdd-Vss | 25°C | -0.3 | 13 | V | |
| Input voltage | Vin | 25°C | -0.3 | Vdd+0.3 | V | |
| Electrical Characteristics | | | | | | |
| Item | Symbol | Condition | Min. | Typ. | Max. | Units |
| Power supply voltage | Vdd-Vss | 25°C | 2.7 | - | 4.5 | V |
| LCD operation voltage | Vop | 25°C | - | 4.8 | - | V |