


PIN NO.	SYMBOL
1	Vss
2	Vdd
3	Vo
4	RD
5	WR
6	A0
7	DB0
8	DB1
9	DB2
10	DB3
11	DB4
12	DB5
13	DB6
14	DB7
15	CS
16	RES
17	Vee
18	FGND
19	NC
20	NC


NOTES:

1. DRIVE METHOD: 1/240DUTY,1/13BIAS,VOP 22.7V,VDD 5V.
2. VIEWING ANGLE: 6 O'CLOCK.
3. DISPLAY TYPE: FSTN, TRANSFLECTIVE/POSITIVE.
4. OPERATING TEMP: -20° TO 70°C.
5. STORAGE TEMP: -30° TO 80°C.
6. IC:SAP3305
7. DC-DC: AIC 1652
8. BACK LIGHT: ORANGE LED B/L
9. TOLERANCE IS ±0.2 UNLESS OTHERWISE NOTED.



DOT SIZE
SCALE 20/1

日期	版本	修改内容
20170413	01	修改公司抬頭為"晶發科技股份有限公司"



晶發科技股份有限公司
GI FAR TECHNOLOGY CO., LTD

DATE	2017.04.13	REV	01		
UNIT : mm	Product :	GFE320240L-FPBE-CD			
SCALE : 1 / 1	DRAWN :				
SHEET : 1 / 1	Hazel				
DRAWN :		Hazel	CHECKED :	Donlin	PAGE : 1 / 1