



RS232

NO.	SIGNAL
1	VDD 5V
2	RXD
3	TXD
4	GND

- NOTES:
1. DRIVE METHOD: 1/64DUTY, 1/9BIAS, VOP 13V,VDD 5V.
  2. VIEWING ANGLE: 6 O'CLOCK, 封口在右.
  3. DISPLAY TYPE: STN(Y-G), TRANSFLECTIVE/POSITIVE.
  4. OPERATING TEMP: -20° TO 70°C.
  5. STORAGE TEMP: -30° TO 80°C.
  6. CONNECTION: ZEBRA.(Large panel is on top layer.)
  7. IC:SBN6400G,SBN0064G.
  8. BACK LIGHT:YELLOW GREEN(VF 4.2V,IF=200mA)
  9. INTERFACE: RS232.
  10. NOT DIMENSION TOLERANCES IS ±0.3.

日期	版本	修改内容
120327	01	修改RS232 PIN的顺序,第一pin在左边,修改PIN脚定义, CN1移除。
121015	02	修改PIN针方向, PIN黑胶部分朝RS232-PCB。
141113	03	修改RS232 PIN位置。
141210	04	增加总高度尺寸标示

晶發科技有 限 公 司  
GI FAR TECHNOLOGY CO., LTD

DATE	2014.12.10	REV	04
UNIT : mm	Product :	GFR192064G-YPAE-D	
SCALE : 1 / 1	DRAWN :	Hazel	CHECKED : Donlin
SHEET : 1 / 1			PAGE : 1 / 1