


PIN	DESCRIPTION
1	VDD
2	VDD
3	RDX
4	D/CX
5	D1
6	D3
7	D5
8	D7
9	RESET
10	CSX
11	D6
12	D4
13	D2
14	D0
15	LED-
16	LED+
17	WRX
18	GND
19	GND

Specification

1. Display mode: 65/262K Colors LCD, Transmissive, Normal White
2. OPERATING TEMP.: -20°C~70°C
3. STORAGE TEMP.: -30°C~80°C
4. LCD DRIVER: ST7735S
5. BACKLIGHT: 1CHIP-WHITE LED, Parallel connection If=15mA
7. UNMARKED TOLERANCE: ±0.20mm
8. REMARK: ROHS
9. SUGGEST: 建議手機機殼V.A開窗比LCD的A.A單邊大於0.50mm

注:
 1.VDD=2.80±0.30V
 2.LED=3.2V Typ., 3.5V Max
 3.亮度: 最小值100cd/m²

日期	版本	修改內容
171201	00	MD圖面


晶發科技股份有限公司
 GI FAR TECHNOLOGY CO., LTD.

DATE	2017.12.01	REV	00	DRAWING NO.:
UNIT : mm	Product : GFT00144DA128128			
SCALE : 1/1	DRAWN:	Hazel	CHECKED:	
				PAGE: 1/1