



Pin Assignment	
1	Ground
2	Ground
3	Data0
4	NC
5	Data1
6	Backlight A(+)
7	Data2
8	Backlight K(-)
9	Data3
10	NC
11	Data4
12	NC
13	Data5
14	IM1
15	Data6
16	NC
17	Data7
18	IOVCC 1.8V
19	Data8
20	IOVCC 1.8V
21	DCX
22	NC
23	RDX
24	VCI 2.8V
25	WRX
26	VCI 2.8V
27	RESX
28	TE
29	CSX
30	NC
31	Ground
32	Ground
33	Ground
34	Ground

Specification

Display Type	TFT/Normally white/TRANSMISSIVE
Display Resolution	DOTS: 240RGB*320
Viewing Angle	6 O'clock
LCD Controller/Driver	ILI9341
Logic Voltage	IOVCC=1.8V; VCI=2.8V
Operation Temperature	-20°C ~ 70°C
Storage Temperature	-30°C ~ 80°C
Backlight Spec.	White LED (4 dies in Parallel) I=60mA V=3.2V
The tolerance unless classified ±0.20mm Remark:ROHS	



日期	版本	修改内容




晶發科技股份有限公司
GI FAR TECHNOLOGY CO., LTD.

DATE: 2017.12.15 REV: 00 DRAWING NO.:

UNIT: mm
SCALE: 1/1

Product: GFT0024IA240320

DRAWN: Hazel CHECKED: Sidney



PAGE: 1/1